

■ Specifications

Parameters	Turbo 100		Turbo 125		Turbo 150 Turbo 160	
	min	max	min	max	min	max
Speed						
Voltage [V / 50 /60 Hz]	1~ 230		1~ 230		1~ 230	
Power [W]	23	25	25	30	42	50
Current [A]	0,10	0,11	0,11	0,13	0,19	0,22
Maximum air capacity [m <sup>3</sup> /h]	170	220	230	345	430	560
RPM [min <sup>-1</sup> ]	1980	2545	1535	2265	1940	2620
Sound pressure level at 3 m distance [dBA]	27	32	29	34	37	46
Max. operating temperature [°C]	60		60		60	
Ingress protection rating	IP X4		IP X4		IP X4	

Parameters	Turbo 200		Turbo 250		Turbo 315	
	min	max	min	max	min	max
Speed						
Voltage [V / 50 /60 Hz]	1~ 230		1~ 230		1~ 230	
Power [W]	76	108	125	177	227	315
Current [A]	0,34	0,48	0,54	0,79	0,99	1,42
Maximum air capacity [m <sup>3</sup> /h]	805	1080	1070	1360	1420	1750
RPM [min <sup>-1</sup> ]	1915	2380	1955	2440	2115	2505
Sound pressure level at 3 m distance [dBA]	45	52	47	55	47	56
Max. operating temperature [°C]	60		60		60	
Ingress protection rating	IP X4		IP X4		IP X4	

■ Overall dimensions

Type	Dimensions [mm]					Weight [kg]
	∅D	∅D1	B	H	L	
Turbo 100	97	164	196	241	303	1,68
Turbo 125	123	164	196	241	258	1,79
Turbo 150	148	187	220	251	289	3,18
Turbo 160	158	187	220	251	289	3,23
Turbo 200	199	209	239	261	295,5	3,8
Turbo 250	247	257	287	323	383	7,83
Turbo 315	310	323	362	408	445	11,7

